

DDR3 Registered DIMM – ULP, VLP & Std. RDIMM



FEATURES:

- 240-pin, dual in-line memory module (RDIMM)
- Proposed JEDEC pin-out
- PC3-12800, PC3-10600, PC3-8500, PC3-6400
- VDD = VDDQ = 1.5V +/- 0.075V
- JEDEC standard 1.5V +/- 0.075V I/O (SSTL_15)
- Operating temperature: 0°C to 85°C
- Industrial temperature range also available
- 8 Banks
- 8-bit pre-fetch architecture
- Bi-directional Differential Data-Strobe
- Programmable Burst Length (8)
- On-die termination (ODT)
- Average Refresh Period 7.8us
- Serial presence detect with EEPROM
- Fly-by topology
- Lead-free, RoHS compliant

BENEFITS:

- Ultra Low Profile
- Low Power
- High densities
- High operational frequency

APPLICATIONS:

- Single Board Computers
- Embedded Computing Platforms
- Telecommunication Servers
- Networking & Storage Appliances
- Military & Aerospace Systems

DESCRIPTION:

Virtium offers DDR3 registered dual in-line memory module (RDIMM) in a selected range of densities, speeds and form factors.

The VLP (Very Low Profile: 0.72" high) and ULP (Ultra Low Profile: 0.70" high) form-factors are well suited for space constrained systems with height restrictions and low airflow requirements.

Virtium RDIMMs are designed to satisfy the demanding memory applications for Embedded, Telecom, Networking, Storage, Military, Aerospace and Ruggedized Computer marketplace.



VLP (Very Low Profile) & ULP (Ultra Low Profile)

DENSITY	HEIGHT	THICKNESS	MAX SPEED	COMP. DENSITY	COMP. PACKAGE	COMP. CONFIG.	MODULE RANKS	CL	PART NUMBER
4GB	0.72"	0.320"	PC3-12800	2Gbit	BGA stack	x4	1	11	VL33B5268E-K0
4GB	0.72"	0.320"	PC3-10600	2Gbit	BGA stack	x4	1	9	VL33B5268E-K9
4GB	0.72"	0.320"	PC3-8500	2Gbit	BGA stack	x4	1	7	VL33B5268E-F8
4GB	0.72"	0.144"	PC3-12800	2Gbit	Monolithic	x8	2	11	VL33B5263E-K0
4GB	0.72"	0.144"	PC3-10600	2Gbit	Monolithic	x8	2	9	VL33B5263E-K9
4GB	0.72"	0.144"	PC3-8500	2Gbit	Monolithic	x8	2	7	VL33B5263E-F8
2GB	0.72"	0.144"	PC3-12800	1Gbit	Monolithic	x8	2	11	VL33B5663E-K0
2GB	0.72"	0.144"	PC3-10600	1Gbit	Monolithic	x8	2	9	VL33B5663E-K9
2GB	0.72"	0.144"	PC3-8500	1Gbit	Monolithic	x8	2	7	VL33B5663E-F8
1GB	0.72"	0.144"	PC3-12800	1Gbit	Monolithic	x8	1	11	VL33B2863E-K0
1GB	0.72"	0.144"	PC3-10600	1Gbit	Monolithic	x8	1	9	VL33B2863E-K9
1GB	0.72"	0.144"	PC3-8500	1Gbit	Monolithic	x8	1	7	VL33B2863E-F8
2GB	0.70"	0.144"	PC3-10600	1Gbit	Monolithic	x8	2	9	VL33B5663F-K9
1GB	0.70"	0.144"	PC3-10600	1Gbit	Monolithic	x8	1	9	VL33B2863F-K9



Standard Height

DENSITY	HEIGHT	THICKNESS	MAX SPEED	COMP. DENSITY	COMP. PACKAGE	COMP. CONFIG.	MODULE RANKS	CL	PART NUMBER
8GB	1.181"	0.144"	PC3-12800	2Gbit	Monolithic	x4	2	11	VL33B1K60A-K0
8GB	1.181"	0.144"	PC3-10600	2Gbit	Monolithic	x4	2	9	VL33B1K60A-K9
8GB	1.181"	0.144"	PC3-8500	2Gbit	Monolithic	x4	2	7	VL33B1K60A-F8
4GB	1.181"	0.144"	PC3-12800	1Gbit	Monolithic	x4	2	11	VL33B5163A-K0
4GB	1.181"	0.144"	PC3-10600	1Gbit	Monolithic	x4	2	9	VL33B5163A-K9
4GB	1.181"	0.144"	PC3-8500	1Gbit	Monolithic	x4	2	7	VL33B5163A-F8
4GB	1.181"	0.144"	PC3-12800	2Gbit	Monolithic	x8	2	11	VL33B5263A-K0
4GB	1.181"	0.144"	PC3-10600	2Gbit	Monolithic	x8	2	9	VL33B5263A-K9
4GB	1.181"	0.144"	PC3-8500	2Gbit	Monolithic	x8	2	7	VL33B5263A-F8
2GB	1.181"	0.144"	PC3-12800	1Gbit	Monolithic	x4	1	11	VL33B5660A-K0
2GB	1.181"	0.144"	PC3-10600	1Gbit	Monolithic	x4	1	9	VL33B5660A-K9
2GB	1.181"	0.144"	PC3-8500	1Gbit	Monolithic	x4	1	7	VL33B5660A-F8
2GB	1.181"	0.144"	PC3-12800	1Gbit	Monolithic	x8	2	11	VL33B5663A-K0
2GB	1.181"	0.144"	PC3-10600	1Gbit	Monolithic	x8	2	9	VL33B5663A-K9
2GB	1.181"	0.144"	PC3-8500	1Gbit	Monolithic	x8	2	7	VL33B5663A-F8
1GB	1.181"	0.144"	PC3-12800	1Gbit	Monolithic	x8	1	11	VL33B2863A-K0
1GB	1.181"	0.144"	PC3-10600	1Gbit	Monolithic	x8	1	9	VL33B2863A-K9
1GB	1.181"	0.144"	PC3-8500	1Gbit	Monolithic	x8	1	7	VL33B2863A-F8

Mechanical Outlines



Unit	Width	Height	Thickness
Inches	5.25	0.70 - 0.72	0.144 - 0.320
Millimeters	133.35	17.78 - 18.29	3.67 - 8.15



Unit	Width	Height	Thickness
Inches	5.25	1.181	0.144 - 0.320
Millimeters	133.35	30.00	3.67 - 8.15

Additional Virtium Memory Products

Virtium DDR3, UDIMM (Unbuffered) with ECC & Non-ECC



- 240-pin, dual in-line memory module
- Standard 1.181" and VLP 0.72" heights
- Unbuffered or UDIMM in 4GB, 2GB and 1GB densities
- Fast data transfer rates: PC3-12800, PC3-10600, PC3-8500 or PC3-6400
- JEDEC Standard form factor
- Targeted for high-speed operations
- RoHS compliance



Virtium Technology provides memory and solid state storage solutions for single board computers and high-reliability systems.

30052 Tomas, Rancho Santa Margarita, CA 92688 USA Tel 949.888.2444 www.virtium.com

Copyright © 2008 Virtium Technology, Inc. All rights reserved. Referenced products are trademarks or registered trademarks of their respective owners.