



| | NAND | 2.5" | M.2 42mm | M.2 60mm | M.2 80mm | mSATA | Slim SATA | 1.8" | CFast |
|--|-------------|--------------------------|-------------------------|-------------------------|-------------------------|------------------------|------------------------|------------------------|-------------------------|
| Dimensions (mm) | | 69.85 x 100.5 x 7/9.5 | 42.15 x 22.15 x 3.65 | 60.15 x 22.15 x 3.65 | 80.15 x 22.15 x 3.65 | 50.80 x 29.85 x 3.7 | 54.00 x 39.00 x 4.0 | 54.00 x 78.25 x 5.0 | 42.80 x 36.40 x 3.30 |
| **Voltage DC | | 5V | 3.3V | 3.3V | 3.3V | 5V | 5V | 3.3V | 3.3V |
| Operating Temp: Standard: -0°C to 70°C Industrial: -40°C to 85°C | | Both | Both | Both | Both | Both | Both | Both | Both |
| Environmental: MIL-STD-810F | | X | X | X | X | X | X | X | X |
| PE (30X*) 5-year Warranty | | | | | | | | | |
| 8GB SATA | SLC | X | X | X | X | X | X | X | X |
| 16GB SATA | SLC | X | X | X | X | X | X | X | X |
| 32GB SATA | SLC | X | X | X | X | X | X | X | X |
| 64GB SATA | SLC | X | X | X | X | X | X | X | X |
| 128GB SATA | SLC | X | - | X | X | X | X | X | X |
| 256GB SATA | SLC | X | - | - | X | X | X | X | X |
| XE (7X*) 5-year Warranty | | | | | | | | | |
| 16GB SATA | pSLC | X | X | X | X | X | X | X | X |
| 30GB SATA | pSLC | X | X | X | X | X | X | X | X |
| 60GB SATA | pSLC | X | X | X | X | X | X | X | X |
| 120GB SATA | pSLC | X | X | X | X | X | X | X | X |
| 240GB SATA | pSLC | X | - | X | X | X | X | X | X |
| 480GB SATA | TLC or pSLC | X | - | - | X | X | X | X | - |
| 960GB SATA | TLC or pSLC | X | - | - | X | X | X | X | - |
| 1920GB SATA | TLC or pSLC | X | - | - | X | X | X | X | - |
| CE (1X*) 3-year Warranty | | | | | | | | | |
| 30GB SATA | MLC | X | X | X | X | X | X | X | X |
| 60GB SATA | MLC | X | X | X | X | X | X | X | X |
| 120GB SATA | MLC or TLC | X | X | X | X | X | X | X | X |
| 240GB SATA | MLC or TLC | X | X | X | X | X | X | X | X |
| 480GB SATA | MLC or TLC | X | - | X | X | X | X | X | X |
| 960GB SATA | MLC or TLC | X | - | - | X | X | X | X | - |
| 1920GB SATA | TLC | X | - | - | X | X | X | X | - |
| 4TB SATA | TLC | X | - | - | - | - | - | - | - |
| 120GB PCIe (AHCI) | MLC | - | X | - | X | - | - | - | - |
| 240GB PCIe (NVMe) | TLC | - | - | - | X | - | - | - | - |
| 480GB PCIe (NVMe) | TLC | - | - | - | X | - | - | - | - |
| 960GB PCIe (NVMe) | TLC | - | - | - | X | - | - | - | - |

* Endurance Baseline = one entire drive write per day for the entire warranty period. ** Wattage is dependent on multiple factors and varies between 1.7 to 3.5 watts. Request product specs for more detail.